

Art.-No. 60050

Cat and Dog Repellent

Help for your cat and dog problems

Get rid of cats and dogs now!

Cats and dogs are the most popular pets in our homes. Whether in the garden or in the living room – they are always welcome and loved. On the other hand there are areas that should be kept pet free like pantries, sandboxes or ponds. The Gardigo Cat and Dog Repellent drives pets away from these areas by using an ultrasonic signal. An infrared motion sensor registers when an animal is in the vicinity and the ultrasound is switched on. The extremely high pitched sound is initially perceived subconsciously by the animal, but eventually it will feel quite uncomfortable with the sound and look for quieter whereabouts. The animals do not feel dislodged and the sound is not doing them any harm. The ultrasonic speaker should be mounted between 10 and 30 cm above ground level.

Gardigo Cat and Dog Repellent was evaluated in the magazine "Heimwerker Praxis" 3/2012 as "good" = 1.5. In the price/performance relationship it was evaluated as "very good".

Conclusion: "Even if it takes a little bit of time until the effect sets in, the animals do eventually react and start looking for other places to do their business" (Translated, Dipl.-Ing. Olaf Thelen)









www.gardigo.de/-60050-Test

Splash-proof for outdoor use!









- Covered area: approx. 7 m
- Frequency: 20 27 kHz
- Motion detector: 70°, 10 m range
- Sound pressure: max. 90 dB
- Battery operation: 6 x AA Mignon batteries (not included)
- Operating display (LED)
- With on/off switch

Additional information


- **Dimensions:** 14 x 8 x 5.5 cm (W x H x D)
- Packaging dimensions: 14.3 x 8.5 x 6.5 cm (W x H x D)
- Manuals included: DE, GB, FR, ES, IT, NL, CZ
- Product video, product images, scenery images
- Packaging unit: 24 units per package





Where do I ideally mount the Gardigo Cat and Dog Repellent Solar?

It depends very much on the purpose and the area you want to cover. In general and in most cases the ideal mounting height is approximately at knee height. The motion sensor and the speakers cover an angle of approximately 70°. If the unit is mounted higher than knee height and not tilted downwards, there is a big blind spot below the device. Placing the device higher and tilted will shorten the range, making sure that the device is not triggered by movements beyond the garden fence. One should always make sure that the motion sensor is not obscured by leaves or other items.



Supplies (optional)

Power supply: Art.-No. 60052





The power supply for the Cat and Dog Repellent must only be used indoors.

Wandhalterung: Art.-Nr. 60056



Use the wall mount to affix the device to the upper parts of a wall. Its angle ensures that the motion sensor can capture movement on the floor.